

VIRTUS MINI AST

Advanced Spraying Technology



– de-icing of roads!

VIRTUS MINI AST

VIRTUS MINI AST

VIRTUS MINI AST is a newly developed liquid spreader, where many years of experience and development have resulted in a new and improved version.

The liquid spreader is width and quantity compensated as well as road-speed related (synchronous), which means that the adjusted spreading quantity per m^2 remains constant irrespective of changes in spreading width or vehicle speed.

Drive by connection to vehicle hydraulic system or petrol engine.

VIRTUS MINI AST is equipped with robust mechanics, plastic components, accurate computer-controlled dosing and a protected spray bar. All mechanical parts are placed on a rear of compartment, which leaves it easy to operate and service.

All spreader functions are controlled by the remote control in the driver's cab, which also makes data collection through EpoTrack possible.

The spreading of a salt solution (NaCl) is the most eco-friendly type of slippery roads control, as liquid spreading reduces the salt consumption considerably.

Liquid spreading provides a quick thawing effect and thus a better friction for vehicles, cyclists and pedestrians. The liquid is distributed evenly and works its way through the frozen surface.

Hopper capacity: 750 - 4500 liters

Spreading width: 1.00 - 5.75 m

Spreading quantity: 10 - 50 ml/m^2
(in steps of 5 ml/m^2)

Road-speed related: 0 - 40 km/h



Stainless spray bar available in 3 sizes:
1 m – 1.3 m – 1.75 m.



Hand lance sprayer for stairs and
hard-to-reach places.



Filling nozzle and liquid level indicator
placed easily accessible.



Epoke® A/S
Vejenvej 50, Askov
DK-6600 Vejen
Tel. +45 76 96 22 00
Fax +45 75 36 38 67
epoke@epoke.dk
www.epoke.dk



In order to maintain the high and uniform product standard Epoke® A/S has been certified by Lloyd's register to ISO 9001:2008.
TLG B-3 approval
GS approval
E1 approval
RoHS directive
WEEE directive


epoke®